

Description

Premium quality primer paints. Fast drying primers for use on on most substrates with exceptional ease of use, resulting in a high quality basecoat, with Vari-Spray nozzles for superb controllability.

Benefits & Features

- Fast drying
- Gives excellent adhesion
- Compatible with most materials
- Can be applied over previously painted surfaces
- High opacity
- Corrosion preventative
- Lead free
- Easy to sand with wet and dry paper
- Vari-spray nozzles for differing spray patterns
- Integral coloured caps for easy identification
- Two mixing balls for fast start up

Directions for Use

Ensure surface is clean, dry and free from grease, rust and loose paint. Prepare with a light sanding for good adhesion. Adjust nozzle for desired spray pattern. Shake can vigorously for 2 minutes and spray a number of light coats with a sweeping action from 25-30cm. Shake can between coats. Primer should be touch-dry and ready for over-coating in 15 minutes. After use, invert can and spray to clear nozzle. **Minimum temperature should be greater than 15°C. Coverage 1.5-2m² per can.**

Technical Data

Appearance:	Red
Odour:	Typical paint aroma
Contents:	Blend of pigments, nitro-cellulose binder, solvents and hydrocarbon propellants
VOC Content:	85% approx
Solids Content:	15% approx
Storage: Flash Point:	Below 50°C
Temperature:	<0°C
	Maximum temperature in use 110°C

Please Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

